

Integrated and decorative

LIGHT FITTINGS

for DAMPA® DCC 300 panel

The DAMPA® DCC light fittings are designed to integrate both aesthetically and functionally with the DAMPA® DCC ceiling system.

All DAMPA® DCC light fittings offer the following main features and advantages:

- Fulfil B-0 classification without additional insulation
- Upgrade to B-15 classification is possible
- Low building/installation height (0-50mm)
- Fast and easy installation
- Delivered in NCS or RAL colour to match ceiling surface
- Lights specified in ceiling layout made by DAMPA

**RIGHT
NOW**

20%

DISCOUNT ON LIGHT FITTINGS,
ON ORDERS PLACED BEFORE
30/12-2020*

DAMPA®

Quiet Danish Design

**RIGHT
NOW**

20%

DISCOUNT ON LIGHT FITTINGS,
ON ORDERS PLACED BEFORE
30/12-2020*

FIND THE PERFECT LIGHT FITTING FOR YOUR PROJECT

Light fitting for DAMPA® DCC 300 Panel



DCC CLASSIC FLUORESCENT TUBE

Don't worry about volt and Hz, one luminaire fits all.

2 x 18W, 110-240V 50/60HZ EL-0. Incl. A6 diffuser

2 x 18W, 110-240V 50/60HZ EL-3. Incl. A6 diffuser

2 x 18W, 220-240V 50/60HZ EL-6. Incl. A6 diffuser

DCC CLASSIC LED TUBE

Delivered incl. replaceable Philips LED tubes.

Long life-time 50.000 hours.

2 x 8W, 220-240V, Kelvin 3000 EL-0. Incl. A6 diffuser

2 x 8W, 220-240V, Kelvin 3000 EL-3. Incl. A6 diffuser

DCC CLASSIC LED BOARD

With replaceable Philips LED technology, five year system warranty.

Long life-time >50.000 hours.

15W, 220-240V, 50/60HZ, Kelvin 3000 EL-0. Incl. A12 diffuser

15W, 220-240V, 50/60HZ, Kelvin 3000, EL-0. Incl. A12 diffuser. DIM

15W, 220-240V, 50/60HZ, Kelvin 3000, EL-24. Incl. A12 diffuser

15W, 220-240V, 50/60HZ, Kelvin 3000, EL-24. Incl. A12 diffuser. DIM

15W, 220-240V, 50/60HZ, Kelvin 3000, EL-24. Incl. A12 diffuser

15W, 220-240V 50/60HZ, Kelvin 3000, EL-6. Incl. A12 diffuser. DIM



DCC SLIM

15W, 220-240V, 50/60HZ, Kelvin 4000, EL-0. Incl. A12 diffuser

15W, 220-240V, 50/60HZ, Kelvin 4000, EL-0. Incl. A12 diffuser. DIM

15W, 220-240V, 50/60HZ, Kelvin 4000, EL-6. Incl. A12 diffuser

15W, 220-240V, 50/60HZ, Kelvin 4000, EL-6. Incl. A12 diffuser. DIM

DAMPA®